

Safety Data Sheet



Date Printed: 7/29/2025

Product: 17176KEP

1. Identification

Product Information: 17176KEP

Product Name: DARK GREEN EPOXY PRIMER, MIL-PRF-23377K TYPE II CLASS N

Recommended Use: Industrial Paint or Paint Related

Application Method: Restricted to professional users

Supplied by: Hentzen Coatings, Inc.
6937 Mill Road
Milwaukee, WI 53218-1225
414-353-4200

Emergency Telephone: ChemTrec 1-800-424-9300

Safety Data Sheet Coordinator: HCI_Regulatory@Hentzen.com

2. Hazards Identification

EMERGENCY OVERVIEW: No hazards to be specially mentioned.

GHS Classification

Carc. 2, Eye Irrit. 2A, Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3 NE, STOT SE 3 RTI

Symbol(s) of Product



Signal Word

Danger

GHS HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Carcinogenicity, category 2	H351	Suspected of causing cancer.

GHS LABEL PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash exposed skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with soap and water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P333+P317	If skin irritation or rash occurs: Get medical help.
P337+P317	If eye irritation persists: Get medical help.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use CO ₂ , dry chemical, or foam to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store in accordance with local regulations.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

GHS SDS PRECAUTIONARY STATEMENTS

P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting/...] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.

3. Composition/Information on Ingredients

Chemical Name	CAS-No.	Wt. %	GHS Symbols	GHS Statements
BARIUM SULFATE	7727-43-7	10-25	No Information	No Information
NATURAL WOLLASTONITE	13983-17-0	10-25	No Information	No Information
METHYL AMYL KETONE	110-43-0	10-25	GHS02-GHS07	H226-302+H332
EPOXY RESIN	25068-38-6	10-25	GHS07	H312-315-317-319
TALC	14807-96-6	2.5-10	No Information	No Information
METHYL ISOBUTYL KETONE	108-10-1	2.5-10	GHS02-GHS07-GHS08	H225-319-332-335-351
EPOXY PHENOL NOVOLAC RESIN	28064-14-4	2.5-10	No Information	No Information
TERTIARY BUTYL ACETATE	540-88-5	2.5-10	GHS02-GHS06	H225-331
CARBON BLACK	1333-86-4	1.0-2.5	GHS07	H332
XYLENE(PURE)	1330-20-7	1.0-2.5	GHS02-GHS07	H226-315
BUTYL ACETATE	123-86-4	0.1-1.0	GHS02-GHS07	H226-336

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - GENERAL ADVICE: Show this safety data sheet to the doctor in attendance. Do not get in eyes, on skin, or on clothing. May cause allergic skin reaction. Call 911 or emergency medical service. Do not delay care and transport of a seriously injured person. Effects should disappear after individual has been exposed to fresh air for approximately 10 minutes. Remove and isolate contaminated clothing and shoes. Consult a physician. Do not breathe vapors, mist or gas. Do not breathe dust. Move out of dangerous area. Use personal protective equipment. Remove all sources of ignition. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin. See section 8 for more information. Ensure adequate ventilation.

FIRST AID - INHALATION: Apply artificial respiration if victim is not breathing. Move victim to fresh air. Keep victim warm and quiet. If unconscious, place in recovery position and seek medical advice. Artificial respiration and/or oxygen may be necessary. Administer oxygen if breathing is difficult. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a doctor immediately if allergic signs, particularly in the respiratory tract, are observed.

FIRST AID - INGESTION: Rinse mouth with water. Consult a physician if necessary. Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice. Allergic symptoms may develop within 12 hours after exposure. Call a poison control center or doctor for treatment advice.

FIRST AID - SKIN CONTACT: Take off contaminated clothing and shoes immediately. Allergic symptoms may develop within 12 hours after exposure. In the case of skin irritation or allergic reactions see a physician. For minor skin contact, avoid spreading material on unaffected skin. In case of contact with substance, keep exposed skin areas immersed in water or covered with wet

bandages until medical attention is received. Remove material from skin immediately. Do not remove clothing if adhering to skin. Wash contaminated clothing before reuse.

FIRST AID - EYE CONTACT: Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. May produce an allergic reaction. In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes. Do not rub affected area. Get medical attention immediately if symptoms occur.

NOTES TO PHYSICIAN: Treat symptomatically. May cause sensitization of susceptible persons. Effects of contact or inhalation may be delayed. Keep victim warm and quiet.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Extremely flammable liquid and vapor. The product causes irritation of eyes, skin and mucous membranes. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Runoff may pollute waterways. Runoff to sewer may create fire or explosion hazard. Vapor explosion hazard indoors, outdoors or in sewers. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Will be easily ignited by heat, sparks or flames. Product is or contains a sensitizer. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cool drums with water spray. Fire will produce dense black smoke containing hazardous combustion products (see section 10). Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Container may explode in heat of fire.

SPECIAL FIREFIGHTING PROCEDURES: No Information

EXTINGUISHING MEDIA: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

6. Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Contain spilled material. Transfer to secure containers. Where necessary, collect using absorbent media. In the event of an uncontrolled release of this material, the user should determine if the release is reportable under applicable laws and regulations. Water spray may reduce vapor; but may not prevent ignition in closed spaces. Dispose of material in accordance with all federal, state and local regulations.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material.

ENVIRONMENTAL PRECAUTIONS: Local authorities should be advised if significant spillages cannot be contained. Should not be released into the environment. Prevent entry into waterways, sewers, basements or confined areas. Prevent spreading of vapors through sewers, ventilation systems and confined areas. See Section 12 for additional Ecological information. Dispose of contents/container to an approved waste disposal plant. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

ADVICE FOR EMERGENCY RESPONDERS: In the event of fire, wear self-contained breathing apparatus. Keep away from sources of ignition. Prevent fire fighting water from entering surface water or groundwater. Cool containers with spray water from a safe distance. Never use welding or cutting torch on or near container (even empty) because product may ignite explosively. Pay attention to flashback. Refer to protective measures listed in sections 7 and 8.

PERSONAL PRECAUTIONS: Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation, especially in confined areas. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges. Pay attention to flashback. All equipment used when handling the product must be grounded. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Wash thoroughly after handling. Contaminated surfaces will be extremely slippery. Refer to protective measures listed in sections 7 and 8. Do not breathe dust. Do not breathe vapors or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8).

7. Handling and Storage



HANDLING: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use spark-proof tools and explosion-proof equipment. Wear personal protective equipment. Remove and wash contaminated clothing before re-use. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). In case of insufficient ventilation, wear suitable respiratory equipment. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Wash thoroughly after handling. Never pierce, drill, grind, cut, saw or weld any empty container. Provide sufficient air exchange and/or exhaust in work rooms. Vapors may form explosive mixtures with air. Prevent the creation of

flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Keep product and empty container away from heat and sources of ignition. Electrical equipment should be protected to the appropriate standard. Keep container closed when not in use. Ground and bond containers when transferring material.

STORAGE: Keep in properly labeled containers. Keep container tightly closed. Keep out of the reach of children. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a well-ventilated place. Keep cool. Ensure all equipment is electrically grounded before beginning transfer operations. Use spark-proof tools and explosion-proof equipment. Keep locked up or in an area accessible only to qualified or authorized persons. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Store between 41 and 77 °F (5 - 25° C) in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA
BARIUM SULFATE	5 mg/m ³	N.E.	15 mg/m ³
NATURAL WOLLASTONITE	1 mg/m ³	N.E.	N.E.
METHYL AMYL KETONE	50 ppm	N.E.	100 ppm
EPOXY RESIN	N.E.	N.E.	N.E.
TALC	2 mg/m ³	N.E.	20 mppcf
METHYL ISOBUTYL KETONE	20 ppm	75 ppm	100 ppm
EPOXY PHENOL NOVOLAC RESIN	N.E.	N.E.	N.E.
TERTIARY BUTYL ACETATE	50 ppm	150 ppm	200 ppm
CARBON BLACK	3 mg/m ³	N.E.	3.5 mg/m ³
XYLENE(PURE)	20 ppm	N.E.	100 ppm
BUTYL ACETATE	50 ppm	150 ppm	150 ppm

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.



SKIN PROTECTION: No special protective equipment required. The selected protective gloves have to satisfy the specifications of EU Regulation (EU) 2016/425 and the standard EN 374 derived from it. Solvent-resistant gloves. Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Follow the skin protection plan. Wear protective gloves/ protective clothing. Wear suitable protective clothing.



EYE PROTECTION: Tightly fitting safety goggles. If splashes are likely to occur, wear: Face-shield.



OTHER PROTECTIVE EQUIPMENT: No Information



HYGIENIC PRACTICES: Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Handle in accordance with good industrial hygiene and safety practice. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin, eyes and clothing. Wash hands before breaks and at the end of workday. Regular cleaning of equipment, work area and clothing is recommended.



ENGINEERING CONTROLS: Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Where reasonably practicable this should be achieved by the use of local exhaust ventilation.

9. Physical and Chemical Properties

Appearance:	Opaque	Physical State:	Liquid
Odor:	Solvent	Odor Threshold:	No Information
Density, lb/gal:	12.571	pH:	No Information
Specific Gravity:	1.515	Viscosity:	No Information
Freeze Point, °C:	No Information	Partition Coefficient, n-octanol/ water:	No Information
Solubility in Water:	No Information	VOC (lb/gal)	2.32
Decomposition temperature, °C	No Information	Explosive Limits, %:	1.0 - 11.4
Boiling Range, °C:	>= 80	Flash Point:	-9 °C / 16 °F
		Auto-Ignition Temperature, °C	No Information

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

REACTIVITY: Flammable.

STABILITY: Stable under recommended storage conditions. Risk of ignition. To avoid thermal decomposition, do not overheat. Keep away from open flames, hot surfaces and sources of ignition.

CONDITIONS TO AVOID: Excessive heat. Storage near to reactive materials. Take precautionary measures against static discharges. Direct sources of heat.

INCOMPATIBILITY: Oxidizing agents. Reducing agents. Risk of explosion if heated under confinement. Vapors are flammable. May form explosive mixtures in air.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

11. Toxicological Information



Practical Experiences

MOST IMPORTANT SYMPTOMS: No Information

EFFECT OF OVEREXPOSURE - INHALATION: No Information

EFFECT OF OVEREXPOSURE - INGESTION: No Information

EFFECT OF OVEREXPOSURE - SKIN CONTACT: May cause sensitization of susceptible persons. May cause allergic skin reaction. May cause sensitization by skin contact. Irritating to skin. May cause skin irritation. Direct skin contact may cause irritation.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Irritating to eyes.

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: No Information

PRIMARY ROUTE(S) OF ENTRY: No Information

CARCINOGENICITY: This product contains a known or suspected carcinogen.

Chemical Name	ACGIH	IARC	OSHA
NATURAL WOLLASTONITE	A4	Group 3	
TALC	A4	Group 2A	X
METHYL ISOBUTYL KETONE	A3	Group 2B	X
CARBON BLACK	A3	Group 2B	X
XYLENE(PURE)	A4	Group 3	

Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Confirmed Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Unclassifiable as to carcinogenicity in humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Acute Toxicity Values**The acute effects of this product have not been tested. Data on individual components are tabulated below**

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
7727-43-7	BARIUM SULFATE	307000 mg/kg Rat	N.I.	N.I.
110-43-0	METHYL AMYL KETONE	1600 mg/kg Rat	10300 mg/kg Rabbit	N.I.
25068-38-6	EPOXY RESIN	11400 mg/kg Rat	2000 mg/kg Rat	99999 mg/l (Vapor)
108-10-1	METHYL ISOBUTYL KETONE	2080 mg/kg Rat	3000 mg/kg Rabbit	N.I.
540-88-5	TERTIARY BUTYL ACETATE	4100 mg/kg Rat	>2000 mg/kg Rabbit	>9.482 mg/L Rat (Vapor)
1333-86-4	CARBON BLACK	>10000 mg/kg Rat	N.I.	4.6 mg/L Rat (Dust)
1330-20-7	XYLENE(PURE)	3500 mg/kg Rat	>4350 mg/kg Rabbit	29.08 mg/L Rat (Vapor)
123-86-4	BUTYL ACETATE	10768 mg/kg Rat	>17600 mg/kg Rabbit	N.I.

N.I. = No Information

12. Ecological Information**ECOLOGICAL INFORMATION:** No Information**PERSISTENCE AND DEGRADABILITY:** No Information**BIOACCUMULATIVE POTENTIAL:** Discharge into the environment must be avoided.**MOBILITY IN SOIL:** No Information**OTHER ADVERSE ECOLOGICAL EFFECTS:** No Information**Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
METHYL AMYL KETONE 110-43-0	No Information	LC50 96 h Pimephales promelas 126 - 137 mg/L	No Information
TALC 14807-96-6	No Information	LC50 96 h Brachydanio rerio >100 g/L	No Information
METHYL ISOBUTYL KETONE 108-10-1	EC50 96 h Pseudokirchneriella subcapitata 400 mg/L	LC50 96 h Pimephales promelas 496 - 514 mg/L	EC50 48 h Daphnia magna 170 mg/L
TERTIARY BUTYL ACETATE 540-88-5	No Information	LC50 96 h Pimephales promelas 296 - 362 mg/L	No Information

XYLENE(PURE) 1330-20-7	No Information	LC50 96 h Pimephales promelas 13.4 mg/L, LC50 96 h Oncorhynchus mykiss 2.661 - 4.093 mg/L, LC50 96 h Oncorhynchus mykiss 13.5 - 17.3 mg/L, LC50 96 h Lepomis macrochirus 13.1 - 16.5 mg/L, LC50 96 h Lepomis macrochirus 19 mg/L, LC50 96 h Lepomis macrochirus 7.711 - 9.591 mg/L, LC50 96 h Pimephales promelas 23.53 - 29.97 mg/L, LC50 96 h Cyprinus carpio 780 mg/L, LC50 96 h Cyprinus carpio >780 mg/L, LC50 96 h Poecilia reticulata 30.26 - 40.	EC50 48 h water flea 3.82 mg/L, LC50 48 h Gammarus lacustris 0.6 mg/L
BUTYL ACETATE 123-86-4	EC50 72 h Desmodemus subspicatus 674.7 mg/L	LC50 96 h Lepomis macrochirus 100 mg/L, LC50 96 h Pimephales promelas 17 - 19 mg/L	No Information

13. Disposal Information



Product

DISPOSAL INFORMATION: Disposal should be in accordance with applicable regional, national and local laws and regulations. Dispose of contents/container to an approved waste disposal plant.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Contain spilled material. Transfer to secure containers. Where necessary, collect using absorbent media. In the event of an uncontrolled release of this material, the user should determine if the release is reportable under applicable laws and regulations. Water spray may reduce vapor; but may not prevent ignition in closed spaces. Dispose of material in accordance with all federal, state and local regulations.

CONTAMINATED PACKAGING: Do not re-use empty containers.

This product contains one or more substances that are listed with the State of California as a hazardous waste:

Chemical Name	CAS-No.
NATURAL WOLLASTONITE	13983-17-0
METHYL AMYL KETONE	110-43-0
TALC	14807-96-6
METHYL ISOBUTYL KETONE	108-10-1
TERTIARY BUTYL ACETATE	540-88-5
CARBON BLACK	1333-86-4
XYLENE(PURE)	1330-20-7
BUTYL ACETATE	123-86-4

14. Transport Information

DOT

UN No	UN1263
Proper Shipping Name:	Paint
Hazard Class:	3
Hazard Subclass:	N/A
Packing Group:	II

IMDG

UN No	UN1263
IMDG/GGVSee Class:	3
EmS-No:	F-E, S-E
Packing Group:	II
Proper Shipping Name:	Paint

Primary Shipping Hazard: No Information
 Marine Pollutant: Not Applicable
 Shipping Hazard(Marine Pollutant): No Information

IATA

UN No UN1263
 ICAO/IATA Class: 3
 Packing Group: II
 Proper Shipping Name: Paint
 Primary Shipping Hazard: No Information

MEX

UN No UN1263
 Proper Shipping Name: Paint
 Hazard Class: 3
 Hazard Subclass: N/A
 Packing Group: II

15. Regulatory Information

U.S. Federal Regulations:**CAA (Clean Air Act):**

U.S. -CAA (Clean Air Act) - 1990 Hazardous Air Pollutants. This product contains the following HAPs:

Chemical Name	CAS-No.
METHYL ISOBUTYL KETONE	108-10-1
XYLENE(PURE)	1330-20-7

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TERTIARY BUTYL ACETATE	N/A	N/A	N/A	X
XYLENE(PURE)	100 lb	N/A	N/A	X
BUTYL ACETATE	5000 lb	N/A	N/A	X

CERCLA - SARA Hazard Category:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372: .

Chemical Name	CAS-No.	Wt %
METHYL ISOBUTYL KETONE	108-10-1	4.30
XYLENE(PURE)	1330-20-7	1.10

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States: All Components of the product are listed or excluded from listing on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) Inventory except as provided below:

No TSCA components exist in this product.

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
BARIUM SULFATE	X	X	X		X
NATURAL WOLLASTONITE					X
METHYL AMYL KETONE	X	X	X		X
EPOXY RESIN					X
TALC	X	X	X		X
METHYL ISOBUTYL KETONE	X	X	X	X	X
EPOXY PHENOL NOVOLAC RESIN					X
TERTIARY BUTYL ACETATE	X	X	X		X
CARBON BLACK	X	X	X	X	X
XYLENE(PURE)	X	X	X	X	X
SYNTHETIC AMORPHOUS SILICA (PRECIPITATED)	X	X	X		
METHYL ETHYL KETONE	X	X	X	X	
BUTYL ACETATE	X	X	X		X
ETHYLBENZENE	X	X	X	X	

CALIFORNIA PROPOSITION 65 CARCINOGENS:**WARNING**

The following ingredients present in the product are known to the state of California to cause Cancer:

Chemical Name

METHYL ISOBUTYL KETONE
CARBON BLACK

CAS-No.

108-10-1
1333-86-4

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS:**WARNING**

The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

Chemical Name

METHYL ISOBUTYL KETONE

CAS-No.

108-10-1

International Regulations: As follows -**INTERNATIONAL INVENTORIES:**

TSCA	-
DSL	Complies
DSL/NDL	Complies
EINECS/ELINCS	-
ENCS	-
IECSC	Complies
KECI	-
PICCS	-
AICS	-
NZIoC	-
TCSI	Complies

Legend:

TSCA	United States Toxic Substances Control Act Section 8(b) Inventory
DSL	Canadian Domestic Substances List
DSL/NDSL	Canadian Domestic Substances List/Canadian Non-Domestic Substances List
EINECS/ELINCS	European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS	Japan Existing and New Chemical Substances
IECSC	China Inventory of Existing Chemical Substances
KECL	Korean Existing and Evaluated Chemical Substances
PICCS	Philippines Inventory of Chemicals and Chemical Substances
AICS	Australian Inventory of Chemical Substances
NZIoC	New Zealand Inventory of Chemicals
TCSI	Taiwan Chemical Substance Inventory

Mexico - Grade Serious risk, Grade 3

Chemical Name	CAS-No.	Carcinogenic Status	Exposure Limits
BARIUM SULFATE	7727-43-7	N/A	Mexico TWA: 10 mg/m3
NATURAL WOLLASTONITE	13983-17-0	N/A	N.D.
METHYL AMYL KETONE	110-43-0	N/A	Mexico TWA: 50 ppm
EPOXY RESIN	25068-38-6	N/A	N.D.
TALC	14807-96-6	A4	Mexico STEL: 2 mg/m3 Mexico TWA: 2 mg/m3
METHYL ISOBUTYL KETONE	108-10-1	A3	Mexico STEL: 75 ppm Mexico TWA: 20 ppm
EPOXY PHENOL NOVOLAC RESIN	28064-14-4	N/A	N.D.
TERTIARY BUTYL ACETATE	540-88-5	N/A	Mexico TWA: 200 ppm
CARBON BLACK	1333-86-4	A3	Mexico TWA: 3 mg/m3
XYLENE(PURE)	1330-20-7	A4	Mexico STEL: 150 ppm Mexico TWA: 100 ppm
BUTYL ACETATE	123-86-4	N/A	Mexico STEL: 200 ppm Mexico TWA: 150 ppm

16. Other Information

Revision Date: 7/29/2025

Supersedes Date: 3/6/2025

Datasheet produced by: Regulatory Department

NFPA Rating:

Health:	2	Flammability:	3	Instability:	0
---------	---	---------------	---	--------------	---

**HMIS Ratings:**

Health:	2*	Flammability:	3	Reactivity:	0	Personal Protection:	X
---------	----	---------------	---	-------------	---	----------------------	---

Volatile Organic Compounds, gr/ltr: 278

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

ObjectId: 56126 88936 191452